





We reserve the right to make technical changes without prior announcement. All rights reserved. ©2019 GENOX RECYCLING TECH (CHINA) CO., LTD.





#11 of No.3 Guangzhu road, Dongchong, Nansha, Guangzhou, China Tel. +86 20 66851345 #810 Fax. +86 20 66851347 e-mail. info@genoxtech.com





GC / GXC / GMC Series

310 6 4106 6310 B

Granulators

GENOX



GENOX

GENOX

www.genoxtech.com

Configurable Rotor Blade Rows GXC Series

The large diameter rotors of the GXC series machines are available with a choice of 5, 7 or 9 rows of rotor blades to suit the specific application. They can therefore achieve the ideal combination of power and cutting efficiency, thus ensuring high throughput volumes and top quality granulated products.





Granulators / GC / GXC / GMC Series











V-Rotor

Our standard open V-Rotor with forward set blades is suitable for processing most types of material. The V-cutting (chevron) configuration of the forward set blades creates a highly efficient, double shear, scissor cutting action.

VB-Rotor

The VB-Rotor with rear set blades is intended for lighter duty applications. The greater shear angle achieved by mounting the blade behind the blade holder results in better performance when processing flexible materials such as plastic films.

C-Rotor

The C-Rotor is a heavy duty, high inertia, semi-closed shaft design which creates a cascade cutting effect. This rotor design is ideal for processing particularly hard or thicker materials, but is also well suited to processing profiles.

CS-Rotor

The CS-Rotor is a particularly open rotor design which allows more area for the material to fall into between each of the staggered blades. This rotor is ideal when processing hollow & bulky materials.

GMC-Rotor


The GMC rotor is specially designed for film and winding material. The staggered blades can cut off the material easily. The design of the rotor creates a good air stream go through the chamber, reducing heat build up within the chamber to aid cooling.

Heavy Duty Granulators GXC Series

GXC Series Heavy Duty Granulators with power ratings of 55kw to 315kw are designed for high throughput processing. With a variety of rotor configurations available, these granulators have a wide range of applications including; hollow and voluminous materials (i.e. plastic drums, crates and chairs), flexible materials such as films, woven bags and rubber, tougher materials such as profiles, thick sheets, and other general plastics.



Auxiliary Flywheel



Sound Proof Enclosure



Hydraulic Opening Device



Granulators / GC / GXC / GMC Series

		GXC Series		
Model	GXC800	GXC1200	GXC1200T	GXC1600T
Dimension (L x W x H) (mm)	2165 × 1780 × 3090	2165 × 2180 × 3090	2490 × 2270 × 3330	$2490 \times 2670 \times 3330$
Hopper Opening (L x H) (mm)	750 × 820	1150 × 820	1150 × 1020	1550 × 1020
Rotation Diameter (mm)	Ø 520	Ø 520	Ø 660	Ø 660
Operation Length (mm)	800	1200	1200	1600
Rotation Speed (RPM)	520	520	520	520
Screen Size(mm)	Ø 12	Ø 12	Ø 12	Ø 12
Number of Rotor Knives	5×2	5×2	7×2	7×4
Number of Counter Knives	3×1	3×2	3×2	3×2
Main Drive (kW)	55~75	75~90	90~132	110~160
Hydraulic Power Pack(kW)	1.5	1.5	1.5	1.5
Weight(kg)	Approx 4400	Approx 5500	Approx 7250	Approx 8500

GXC Series					
Model	GXC1200G	GXC1600G	GXC2000G		
Dimension (L x W x H) (mm)	$2650\times2470\times3900$	2650 × 2870 × 3900	2650 × 3270 × 3900		
Hopper Opening (L x H) (mm)	1160 × 1150	1560 × 1150	1960 × 1150		
Rotation Diameter (mm)	Ø 800	Ø 800	Ø 800		
Operation Length (mm)	1200	1600	2000		
Rotation Speed (RPM)	480	480	480		
Screen Size(mm)	Ø 12	Ø 12	Ø 12		
Number of Rotor Knives	9×2	9×4	9×4		
Number of Counter Knives	3×2	3×2	3×4		
Main Drive (kW)	110~160	160~250	250~315		
Hydraulic Power Pack(kW)	1.5	1.5	1.5		
Weight(kg)	Approx 9300	Approx 11800	Approx 15500		

Granulators GC Series

GC Series Granulators are high speed granulation machines designed especially for the efficient size reduction of various materials in a single pass. These machines are ideal for processing a multitude of materials including plastics, rubber, fibers, copper cable and light non-ferrous metals amongst others.



PVC



PFT



GC Series					
Model	GC600T	GC800	GC800T		
Dimension (L x W x H) (mm)	1380 × 1170 × 2200	1380 × 1370 × 2200	1580 × 1440 × 2300		
Hopper Opening (L x H) (mm)	560 × 615	760 × 615	760 × 615		
Rotation Diameter (mm)	Ф320	Ф320	Ф420		
Operation Length (mm)	600	800	800		
Rotation Speed (RPM)	580	580	580		
Screen Size(mm)	Ф12	Φ12	Ф12		
Number of Rotor Knives	3×2	3×2	3×2		
Number of Counter Knives	2×1	2×1	2×1		
Main Drive (kW)	22	30	37		
Weight(kg)	Approx 1500	Approx 1800	Approx 3000		

Granulators GMC Series

GMC Heavy Duty Granulators are designed for high throughput size reduction of larger sized products in a single pass. These machines are specifically designed for treating plastic film or PP big bag material of high contamination. Incorporating various different methods of wear protection such as replaceable wear plates and resistant surface coatings, the GMC machines are well suited to processing abrasive, contaminated materials such as glass filled plastics and dirty films containing sands.



PP PLASTIC FILM



PP WOVEN BAG



GMC Series					
Model	GMC800	GMC1000			
Dimension (L x W x H) (mm)	2165 × 1780 × 3090	2165 × 1980 × 3090			
Hopper Opening (L x H) (mm)	760 × 615	950 × 810			
Rotation Diameter (mm)	520	520			
Operation Length (mm)	800	1000			
Rotation Speed (RPM)	520	520			
Number of Rotor Knives	8	8			
Number of Counter Knives	2	4			
Main Drive (kw)	55	75			
Weight (kg)	5580	6180			

Benelux distributeur:

