




Flexible Screw Feeder

SSC-50 & MST-S



Refer carefully to the manual before operation.


■ Coding Principle



Material Outlet

■ Features

- Effectively avoid material stratification during conveying process
- Fully closed conveying line, free from contamination
- Flexible conveying line brings maximum convenience of installation, best compatibility with other conveying equipments
- Reverse phase protector is adopted to avoid that the motor is working in the reverse direction.
- Standard conveying pipeline is 5m/197.5 inch which can reach be lengthened to 7m/276 inch.




■ Application

SSC series flexible screw feeders adopt motor-driven screws for raw material conveying, applicable to convey regrinds, virgin materials, powders and their mixtures with features of easy installation and maintenance. It can work with other Shini's products, such as PET crystallizer, and blender (must be mounted on the customized flange). Two models of SSC-50/65 available with max. horizontal conveying capacity of up to 1,900 kg/hr (4,189 lb/hr).

SSC Series

Outline Drawings



Specifications

Model	Outer Dia.		Motor Power (kW, 50/60Hz)	Motor Rotating Speed (RPM, 50/60Hz)	Radius		Bulk Density		Material	Conveying Capacity(50/60Hz)			
	mm	inch			mm	inch				A=0°		A=45°	
SSC-50	Φ 50	Φ2	0.75/0.85	910/1090	1,500	59	0.8	6.7	Pellet	800/ 900	1,764/ 1,984	700/ 840	1,543/ 1,852
							0.7	5.8	Powder	450/ 540	992/ 1,190	350/ 420	772/ 926
							0.3	2.5	Flake	300/ 360	661/ 794	250/ 300	551/ 661
SSC-65	Φ 65	Φ2.5	1.1/1.26	910/1090	1,500	59	0.8	6.7	Pellet	1,900/ 2,280	4,189/ 5,026	1,400/ 1,680	3,086/ 3,074
							0.7	5.8	Powder	1,000/ 1,200	2,205/ 2,646	800/ 960	1,543/ 2,116
							0.3	2.5	Flake	600/ 720	1,323/ 1,587	500/ 600	1,102/ 1,323

Notes: 1) Bending radius of conveying pipeline should be more than 1.5m/59inch and its bending angle should be more than 120° to prevent overload, material blockage or spring fracture.

2) To be conveyed granule dia. : For SSC-50, it should be less than 4mm/0.16inch and for SSC-65, it should be less than 6mm/0.24inch or material could easily get stuck. Also we suggest not use it to convey flakes with more than 15mm in/0.59inch length.

3) Power supply: 3Φ, 230/400/460/575V, 50/60Hz.

Shini Group

Addr: No. 23, Minhe St., Shulin Dist.,
New Taipei, Taiwan

Tel: +886 2 2680 9119

Fax: +886 2 2680 9229

Email: shini@shini.com

Factories:

- Taiwan
- Dongguan
- Pinghu
- Ningbo
- Chongqing
- Pune